



## DSP-2060A



### DESCRIPTION

The DSP-2060A is a powerful DSP based audio processor, ideally suited for install and live applications, where it combines the functions of a multitud of conventional products in a compact unit.

### KEY FEATURES

- 2 inputs and 6 outputs
- 9 full bandwidth parametric bands on each output
- 8 full bandwidth parametric bands on each input
- 48 dB/oct crossover filters on each output
- Adjustable gain on both inputs and outputs
- RS232 and RS485 ports
- Remote control via AudioCore and DASnet™

### APPLICATIONS

- House of worship
- Theatres, auditoria and performing arts centers
- Live music clubs
- Corporate A/V
- Live sound touring/Rental services

### SPECIFICATIONS

#### Electronics and Connectors

CMRR	>65dB, 50 Hz to 10 kHz
Total Harmonic Distortion	<0.02% @ 1KHz +18dBm
Sampling Rate	96 kHz
Crossover Filters	6, 12, 18, 24, 48 dB/oct Bessel, Butterworth, Linkwitz-Riley
Limiter Attack Time	Variable
Limiter Release Time	Variable
Limiter Threshold	+22 dBu to -10 dBu
Maximum Delay	650 ms
Maximum Output Level	+20 dBm into 600 ohms
Output Gain	+15 dB to -40dB in 1 step
Current Draw 230 V	a:0:}
Audio Signal Input Connector	2 x Female XLR RS485 In/Out XLRs RS232 9 Pin (Female) D Connector
Certification Number	CB GB-6949-Z/M1

#### Dimensions-Weight

Dimensions ( H x W x D )	44 x 482 x 300 mm 1,7 x 19,0 x 11,8 in
Net Weight	3,3 kg ( 7,3 lb )

#### Shipping

Carton Dimensions ( H x W x D )	110 x 530 x 450 mm 4,3 x 20,9 x 17,7 in
---------------------------------	--



# DSP-2060A

Shipping Weight

4,5 kg ( 9,9 lb )

## ORDERING INFORMATION

Model	Description	P/N
<b>System</b>		
DSP-2060A		11105030

## DIMENSIONS

