# **QUANTUM** series



# **Q-3-TW**



#### **DESCRIPTION**

The Q-3 is a highly compact and discrete system ideal for short distances, for creating ambience, and for frontfill and underbalcony sound reinforcement. Like the other systems in the series, the Q-3 has two operating modes (voice and music) that guarantee outstanding speech intelligibility and excellent music reproduction in any acoustic environment.

The aluminum enclosure and the IP-66 kit make this a highly reliable and durable choice, available in any RAL color.

#### **KEY FEATURES**

- · Passive system
- · Extruded aluminum enclosure
- ·1 x 3", 3P full-range speaker
- · Dispersion H x V: 120° x 120°
- · SPL peak: 106 dB
- · Multi-tap 100/70V transformer included
- · Low/high-impedance operation
- · Available in all RAL colors

#### **APPLICATIONS**

- $\cdot$  A/V systems and corporate events
- · Meeting rooms, classrooms, and exhibit areas
- · Installations in bars and clubs

### **SPECIFICATIONS**

| Performance                      |  |  |
|----------------------------------|--|--|
| Frequency Range (-10 dB)         | 150 Hz - 20 kHz                          |  |
| Horizontal Coverage (-6 dB)      | 120°                                     |  |
| Vertical Coverage                | 120°                                     |  |
| Nominal Impedance                | 8 ohms                                   |  |
| Transformer Taps 70 V            | 3.5 W - 7.5 W - 10 W                     |  |
| Transformer Taps 100 V           | 7.5 W - 15 W - 20 W                      |  |
| RMS Power Handling               | 20 W                                     |  |
| Peak Power Handling              | 80 W                                     |  |
| On-axis Sensitivity 1W/1 m       | 87 dB SPL                                |  |
| Maximum Peak SPL at 1 m          | 106 dB SPL                               |  |
| Recommended Amplifier            | INTEGRAL-A402<br>INTEGRAL-A404           |  |
| Recommended Processor            | DSP-226                                  |  |
| Connectors Audio Input Connector | 4-way Phoenix 2.54 mm                    |  |
| Enclosure Enclosure Construction | Aluminum                                 |  |
|                                  |  |  |
| Color                            | White                                    |  |
| IP Rating                        | IP66                                     |  |
| Depth                            | 125 mm (4,9 in)                          |  |
| Dimensions ( H x W x D )         | 105 x 125 x 125 mm<br>4,1 x 4,9 x 4,9 in |  |



 Net Weight
 1,6 kg (3,5 lb)

 Components
 MF Driver

 3P

# **ORDERING INFORMATION**

| Model             | Description                  | P/N      |
|-------------------|------------------------------|----------|
| System            |                              |          |
| Q-3-TW            |                              | 10434010 |
| Replacement Parts |                              |          |
| 3P                | Cone Transducer              | 20208711 |
| F-Q-3-T           | Filter                       | 20140140 |
| LAMP-F-21         | Lamp                         | 30000535 |
| Accessories       |                              |          |
| AXC-AT2           | Installation & Stacking Acc. | 10104311 |
| AXC-Q-W           | Installation & Stacking Acc. | 10105147 |
| AXC-ZT2           | Installation & Stacking Acc. | 10104325 |
| AXW-4-W           | Installation & Stacking Acc. | 10104173 |
| AXW-5-W           | Installation & Stacking Acc. | 10104174 |
| JP-Q-W            | Installation & Stacking Acc. | 10102974 |
| KIT-IP-Q-W        | Installation & Stacking Acc. | 10434091 |
|                   |                              |          |

# **DIMENSIONS**









