### PM-35USB

Order No. 1000673



**Dynamic microphone,** with USB connector.

- For operating directly at a PC
- No driver installation required, device will be identified automatically
- Microphone cartridge with cardioid polar pattern
- Integrated A/D converter (16 bits/48 KHz)
- On/off switch
- For Windows XP/Vista/Win7/Win10 or Mac

Model	PM-35USB
Polar pattern	cardioid
System	dynamic
Audio frequency range	100-10,000 Hz
Nominal impedance	600 Ω
Sensitivity	2.5 mV/Pa
Max. sound pressure	145 dB
Housing material	plastic
Dimensions	Ø 50 mm x 200 mm
Weight	202 g
Cable	4 m, assembled
Connection	plug Type-A



# CM-601

Order No. 0235010

### **Electret boundary microphone**

- For theatrical performances, discussions, conferences and in churches
- A direct alignment to the sound source is not essential due to the special characteristics of a boundary microphone
- Dual low cut filter (80 Hz/120 Hz)
- Configurable push-button (PTT, PTM or switching function)
- Standby LED
- Robust and shock-absorbing body
- Elastic cartridge suspension for preventing structure-borne noise and impact sound

CM-601
cable
semi-cardioid
electret
30-12,000 Hz
100 Ω
2.2 mV/Pa
125 dB
= 15-48 V, phantom power
diecast metal
0.85 kg
3-pin mini XLR plug, unbal.

- With 8 m cable mini XLR jack to XLR plug
- Connection via 3-pin mini XLR plug, unbal.
- With preformed outline at the bottom for possible wall
  mounting.



## CM-602USB

Order No. 0231870



## **Electret boundary microphone,** with USB port.

- On/off switch with power LED
- Elastic cartridge suspension for preventing impact sound and structure-borne noise
- With 1.8 m USB connection cable

Model	CM-602USB	
Polar pattern	semi-cardioid	
System	electret	
Audio frequency range	30-12,000 Hz	
Nominal impedance	100 Ω	
Sensitivity	2.2 mV/Pa	
Max. sound pressure	125 dB	
Power supply	via USB interface	
Housing material	plastic	
Dimensions	72 x 23 x 110 mm	
Weight	88 g	
Cable	1.8 m	
Connection	USB type B jack	

