

# Professional Audio Cable TPS7182/TPS7222

TATSUTA TACHII PROSOUND JAPAN



## The Top Analog Audio Cable of the New Era TPS 7182 / TPS 7222

Fully integrated production from conductor manufacturing to assembly at our own factory.  
 The world's highest level of low impedance characteristics improve the latency in milliseconds.  
 Conducted absolute on-site tests for adjusting cushioning materials.  
 The signal will not interrupted even when the cable is caught in the soundproof doors.  
 Reduce the background noise of 30Hz-80Hz caused by cables.  
 Easy to operate bandwidth adjustments without relying on HPF.  
 TPS improves the sound density problems and the sound pressure which is caused by phase interface.

### TPS 7182

NEXT BENCHMARK, HI PERFORMANCE



The world class low impedance of  $2.9\Omega/100m$ .  
 The high density and the low latency fit the hi-bit generation.  
 TPS promise the high accuracy sound.

### TPS 7222

REAL STANDARD AT ALL SOUND FIELD



Better impedance than other same class products by 30%.  
 Overtone components of tuned low-frequency realized  
 easy operation.

- In-house manufactured high density copper conductor
- Tinned annealed mesh shield
- 100% Cotton shock mount
- Soft PVC sheath



	OD	Size / AWG	Conductor construction	No. of cores	Conductor resistance	Insulation	Shield	Sheath
TPS 7222	6.1mm	0.30mm / 22	12 / 0.18A	2	6.90Ω / 100m@20°C	PVC	Tinned annealed copper wire	PVC
TPS 7182	6.9mm	0.75mm / 18	30 / 0.18A	2	2.64Ω / 100m@20°C	PVC	Tinned annealed copper wire	PVC

TATSUTA TACHII make your "PROSOUND"